

Lightning-fast printing with large working area

- fast printing
- · a large working area
- · access to the full range of materials
- open environment
- tiltable screen
- · cargo-type pull-out transfer overflow bin



GENERAL

OLINEINAL		
Technology	SLS - Selective Laser Sintering	
Laser type	IR Fiber Coupled Diode Laser, 30W; λ = 976 ± 3 [nm] rated to > 30,000 hrs	
Laser scanner type	Galvo	
Dimensions	650x610x1200 [mm] (25.6x24.0x47.2 [in])	
Weight	145 [kg] (319.7 [lbs])	
PRINT VOLUME		
Max size of print diagonally ¹	398 [mm] (15.7 [in])	
Max print volume	TPU based / Flexible materials: 130x180x340 [mm] (5.1x7.1x13.3 [in]) PA / PP: 130x180x330 [mm] (5.1x6.7x13.3 [in])	
PRINTER PARAMETERS		
Size of Print Bed	150x200x350 [mm] (5.9x7.9x13.8 [in])	
Layer height Z (min - max)	0.075 - 0.175 [mm] (0.003 - 0.006 [in])	
Build Speed	up to 14 [mm/h] (0.55 [in/h])	
PRINT FEATURES		
Min. wall thickness	from 0.5 [mm] (0.020 [in])	
Hole diameter	from 0.5 [mm] (0.020 [in])	
Moving part clearance	from 0.2 [mm] (0.008 [in])	

Information provided within this document are typical values for reference and comparison only. Parameters presented in this data sheet are subject to change. Final part properties may vary based on printed part design and print orientation. Material during tests - parameters are subject to change.



ADDITIONAL PRINTER FEATURES

ADDITIONAL PRINTER FEATURES		
Inert gas control system	built-in	
Average inert gas consumption	0.48 [m³/h] = 8 [l/min.]	
SOFTWARE		
Software ²	Sinterit Studio	
Supported file types	STL, 3MF, OBJ, 3DS, FBX, DAE	
Output file types	*.scode, *.sspf, *.sspfz	
OS compatibility	Microsoft Windows 10 or higher	
COMMUNICATION		
LCD screen	9" interactive touchscreen	
On-board camera	Built-in	
Connectivity	WiFi / Ethernet / USB	
HEATING SYSTEM		
Independent	4 modifiable zones: print chamber , print surface, cylinder and piston - 16 independent heating elements	
Max temperature in the chamber	210 [°C] / 410 [°F]	
POWER		
Operating voltage	230 [V] AC, 50/60 [Hz], 8 [A] or 100-120 [V] AC, 50/60 [Hz], 15 [A]	
Average power consumption	ge power consumption 0.85 [kW]	
Max power consumption	1.65 [kW]	
PACKAGING		
Size of package	650x750x1350 [mm] (25.6x29.5x53 [in])	
Package weight	190 [kg] (418 [lbs])	
WARRANTY		
Warranty period	One year limited	

SOFTWARE VERSIONS

Available:	Sinterit Studio	Sinterit Studio ADVANCED
Powder profiles	PA12 Smooth, Flexa Grey only	✓ All available
Possibility to use 3rd party materials	-	✓
Open Printing Parameters	_	✓

 $^{^{1}}$ Max size of print diagonally depends on the type of material. 2 Technical requirements to install Sinterit Studio Software: Windows 10 or higher / Minimum 500 MB of disk space / Minimum 2 GB of RAM / Graphics adapter compatible with OpenGL 3.0 or higher.

